

10/565091

IAP20 Rec'd PCT/PTO 18 JAN 2006

Claims:

1. Screen for holding refuse sacks (7) open, c h a -
r a c t e r i z e d i n

that the screen (1) is shorter than the refuse sack
(7) such that open parts (7b) of the refuse sack (7) can
5 be folded into the screen (1),

that the screen (1) is designed to stretch the re-
fuse sack (7), and

that a locking device (11) is provided on the screen
(1) such that open parts (7b) of the refuse sack (7) can
10 be pressed on said locking device (11).

2. Screen according to claim 1, c h a r a c t e -
r i z e d i n

that the screen (1) consists of elastic material
and is compressible from a normal shape to a narrower
15 shape,

that the refuse sack (7) can be threaded onto the
screen (1) or said screen (1) be inserted into said re-
fuse sack (7) when said screen (1) is compressed to a
narrower shape, and

20 that the screen (1) can be brought to spring out
from its narrower shape to its normal shape and thereby
stretch the refuse sack (7).

3. Screen according to claim 2, c h a r a c t e -
r i z e d i n that a holding-together member (13) is
25 provided to hold the screen (1) in its narrower shape.

4. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that second end portions (1c)
of the screen (1) has at least one handle opening (6)
into which parts (12) of the refuse sack (7) are insert-
30 able such that one can get hold of the handle opening (6)
in order to lift and carry the screen (1) and the refuse
sack (7).

5. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that the locking device (11)
35 comprises pins (11a) which extend outwards from second

04-03-2005

end portions (1c) of the screen (1) and against which open parts (7b) of the refuse sack (7) can be pressed preferably for penetration thereof.

6. Screen according to any preceding claim, c h a -
5 r a c t e r i z e d i n that the screen (1) in cross section has a semicircular or substantially semicircular shape.

7. Screen according to claim 1, c h a r a c t e -
r i z e d i n that the screen (1) is provided to permit
10 location thereof, with a refuse sack (7) provided thereon, on a support (8) from which refuse shall be moved into the refuse sack (7), such that those parts (12) of the refuse sack (7) which extend between the two longitudinal edges (2, 3) of the screen (1) and which thereby have a
15 planar or substantially planar shape, are situated close to and/or engage said support (8).

8. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that the longitudinal edges
(2, 3) of the screen (1) are designed or include members
20 for preventing damage of the refuse sack (7) by said longitudinal edges (2, 3).

9. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that a strip (15) can be hoo-
ked onto two longitudinal edges (2, 3) of the screen (1)
25 such that said strip (15) extends across an opening (1a) between said edges (2, 3) at second end portions (1c) of the screen (1) and that open parts (7b) of the refuse sack (7) can be folded within said strip (15).

10. Screen according to any preceding claim, c h a -
30 r a c t e r i z e d i n

that the screen (1) is thin-walled and elastic and consists of polypropylene or similar material, and

that the refuse sack (7) is a plastic bag from which the screen (1) can be removed and which can be
35 tied up after removal of the screen (1).

[received by the International Bureau on 31 January 2005 (31.01.2005)]

Claims 1 was amended

(total 2 pages)]

1. Screen for holding refuse sacks (7) open, c h a -
r a c t e r i z e d i n

that the screen (1) is shorter than the refuse sack
(7) such that open parts (7b) of the refuse sack (7) can
5 be folded into the screen (1),

that the screen (1) is designed to stretch the re-
fuse sack (7), and

that a locking device (11) is provided on the screen
(1) such that open parts (7b) of the refuse sack (7) can
10 be pressed on said locking device (11).

2. Screen according to claim 1, c h a r a c t e -
r i z e d i n

that the screen (1) consists of elastic material
and is compressible from a normal shape to a narrower
15 shape,

that the refuse sack (7) can be threaded onto the
screen (1) or said screen (1) be inserted into said re-
fuse sack (7) when said screen (1) is compressed to a
narrower shape, and

20 that the screen (1) can be brought to spring out
from its narrower shape to its normal shape and thereby
stretch the refuse sack (7).

3. Screen according to claim 2, c h a r a c t e -
r i z e d i n that a holding-together member (13) is
25 provided to hold the screen (1) in its narrower shape.

4. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that second end portions (1c)
of the screen (1) has at least one handle opening (6)
into which parts (12) of the refuse sack (7) are insert-
30 able such that one can get hold of the handle opening (6)
in order to lift and carry the screen (1) and the refuse
sack (7).

5. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that the locking device (11)
35 comprises pins (11a) which extend outwards from second

9.

end portions (1c) of the screen (1) and against which open parts (7b) of the refuse sack (7) can be pressed preferably for penetration thereof.

6. Screen according to any preceding claim, c h a -
5 r a c t e r i z e d i n that the screen (1) in cross section has a semicircular or substantially semicircular shape.

7. Screen according to claim 1, c h a r a c t e -
r i z e d i n that the screen (1) is provided to permit
10 location thereof, with a refuse sack (7) provided thereon, on a support (8) from which refuse shall be moved into the refuse sack (7), such that those parts (12) of the refuse sack (7) which extend between the two longitudinal edges (2, 3) of the screen (1) and which thereby have a
15 planar or substantially planar shape, are situated close to and/or engage said support (8).

8. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that the longitudinal edges
(2, 3) of the screen (1) are designed or include members
20 for preventing damage of the refuse sack (7) by said longitudinal edges (2, 3).

9. Screen according to any preceding claim, c h a -
r a c t e r i z e d i n that a strip (15) can be hoo-
ked onto two longitudinal edges (2, 3) of the screen (1)
25 such that said strip (15) extends across an opening (1a) between said edges (2, 3) at second end portions (1c) of the screen (1) and that open parts (7b) of the refuse sack (7) can be folded within said strip (15).

10. Screen according to any preceding claim, c h a -
30 r a c t e r i z e d i n

that the screen (1) is thin-walled and elastic and consists of polypropylene or similar material, and

that the refuse sack (7) is a plastic bag from which the screen (1) can be removed and which can be
35 tied up after removal of the screen (1).